

FIRE FIGHTER I JPR: FFI-3N

PERFORMANCE OUTCOME: Equipment Require Conditions: Given a No. CHECK: FIRE HY 1. Connect su 2. Connect su	team, giver source, so The candidate, while operating supply hose, connect and place as well as the equipment necess oumper hose connections for foopen and close the hydrant. Safety: A safety violation is grathe safety violation. d: Full PPE, appropriate equipal static water source or fire hydrant Fire Hydrant DRANT CONNECTION VIA	as a member of a tea hard suction hose for sary to transfer water orward and reverse la rounds for automat oment for hydrant or s rant, the candidate sh	r drafting operations, dep between and draft from t tys, connect supply hose t tic failure. All proctors p static water supply. hall demonstrate the abilit Static Water Source	hydrant or stat nobstructed. ability to hand bloy portable w them, make hy- to a hydrant, ar present shall r	lay a lay a vater tanks drant-to- nd fully	
PERFORMANCE OUTCOME: Equipment Require Conditions: Given a No. CHECK: FIRE HY 1. Connect su 2. Connect su	The candidate, while operating supply hose, connect and place as well as the equipment necess number hose connections for foopen and close the hydrant. Safety: A safety violation is grathe safety violation. d: Full PPE, appropriate equipal static water source or fire hydrant Fire Hydrant DRANT CONNECTION VIA	hard suction hose for sary to transfer water orward and reverse la rounds for automatement for hydrant or sarnt, the candidate shares or	r drafting operations, dep between and draft from t tys, connect supply hose t tic failure. All proctors p static water supply. hall demonstrate the abilit Static Water Source	ploy portable withem, make hydrant, and a hydrant, and present shall i	vater tanks drant-to- nd fully	
No. CHECK: FIRE HY 1. Connect su 2. Connect su	Fire Hydrant DRANT CONNECTION VIA	rant, the candidate sh Task Steps or	nall demonstrate the abilit	ty to:	✓	
No. CHECK: FIRE HY Connect su Connect su	Fire Hydrant DRANT CONNECTION VIA	Task Steps or	Static Water Source	ty to:	√	
CHECK: FIRE HY 1. Connect su 2. Connect su	DRANT CONNECTION VIA	or			√	
1. Connect su 2. Connect su	DRANT CONNECTION VIA					
1. Connect su 2. Connect su		A FORWARD & RE	EXTED CIE I AX		1	
2. Connect su	ipply hose to hydrant.		EVERSE LA I			
l	Connect supply hose to hydrant.					
3. Fully open	Connect supply hose to pumper intake.					
J 1	Fully open hydrant.					
4. Fully close	Fully close the hydrant.					
STATIC V	STATIC WATER SOURCE					
1. Deploy po	Deploy portable water tank.					
2. Check gash	Check gaskets on the hard suction hose for dirt, gravel or defects.					
3. Connect st	Connect strainer to hose.					
4. Connect ha	Connect hard suction hose to pumper.					
5. Lower hos	e and strainer into static water s	source.				



Candidate:

FIRE FIGHTER I JPR: FFI-5B

STANDARD: 4.5.2			Task: Clean, inspect, and return fire hose to service, given washing equipment,					
NFPA 1001, 2019 Edition		ition	water, detergent, tools, and replacement gaskets, so that damage is noted and					
Duran and Maladana		[a:tamamaa	corrected, the hose is clean, and the equipment is placed in a ready state for					
Preparedness, and Maintenance			service.					
PERFORMANCE and drying equiper and reload hose.			all demonstrate the ability to clean different types of hose, operate hose washing					
		and drying equipment (if available), mark defective hose, and replace coupling gaskets, roll hose,						
		Safety: A safety violation is grounds for automatic failure. All proctors present shall review						
		the safety violation		Teview				
Equip	ment Required	l: Fire apparatus, so	crub brush, hose, cleaning supplies, replacement gaskets, hose washer an	d dryer				
(if available), log book or tags for reporting repair needs, and personal protective clothing (proctor to determine what PPE								
is to be	e worn).							
COND	OITIONS: Giv	en Fire Department	hose and apparatus, the candidate shall demonstrate the ability to:					
No.			Task Steps	✓				
	INSPECT / C	CLEAN HOSE						
1.	Inspect / Cl	ean hose.						
2.	Inspect / Clean couplings according to department guidelines.							
3.	Dry hose.							
4.	Place in ready state and report any deficiencies.							
RETURNING HOSE TO SERVICE								
5.		Roll	hose as selected by proctor (Check one):					
	Straight	Donut	Twin Donut Self-Locking Twin Donut					
6.	Reload hose on apparatus using a hose load specific to apparatus or department:							
	Pre-connect							
	Supply Line)						
Evaluat	Evaluator (Print & Sign) Date:							